

Corner originally set as a post in 1820 by Wm. B. Laughlin with the following witnesses: 11" elm bearing north 72 degrees, thence east 33 links; and a 6" ash bearing south 55 degrees, thence west 19 links.8 (M.C.Atlas p.9) A survey by H.B.Fatout on August 16,1877 indicates a stone with the following witnesses: 8"gray ash bearing north 28 degrees, thence west 33.50 links; and a 6"gray ash bearing north 30 degrees, thence east 39.50 links; and a 22" elm bearing south 44 degrees, thence west 69 links.(Perry Legal Book p.12) A survey by Paul Julian on May 16, 1894 indicates a stone. (Perry Legal Book p. 50) Corner referenced by MCS on 12/18/43 and called an iron pin. Corner referenced by SeFranka on 5/21/70 and called a R.R.spike. Corner referenced by Fortner on 6/30/75 and called a R.R.spike. Corner referenced by Wilcoxen on 1/13/87 and called a R.R.spike. Corner referenced by Gries on 9/18/87 and called a R.R.spike. Corner referenced by Wilcoxen on 3/24/93 and called a R.R.spike. Corner referenced by Wilcoxen on 10/23/98 and called a R.R.spike. Corner excavated by Wilcoxen on 10/23/02 and a mag nail was found at the surface. A R.R. spike was found 3" down. A steel pin was found 8" down. A #205 cast iron Harrison monument was set in position as the corner. No stone was found.

REF.	DISTANCE	DESCRIPTION
1.	174.90'	Mag nail w/brass washer N PwP#70-730 40"up
2.	23.50	Mag nail w/bw E PwP#77-730 24"up
3.	170.84	Top nut of fire hydrant
4.	50.94	PK nail E PwP no# 24"up
5.	109.06	Corner fence post